



Ropox Swing Washbasin and Dock-in User Manual & Mounting Instructions

This manual should always be in close proximity of the product.

Table of content

1.	SYMBOLS USED IN THIS MANUAL	3
2.	GENERAL SAFETY	3
	2.1 Product Unit label	5
3.	GENERAL REQUIREMENTS	6
	3.1 Product information	6
	3.2 Product description.....	6
	3.3 Intended use.....	6
	3.4 Intended operator	6
	3.5 Essential performance.....	7
	3.6 Non-clinical functions	7
	3.7 Clinical functions	7
	3.8 Product dimensions.....	7
	3.9 Connection adapters	8
	3.10 Layout proposals	9
4.	INSTRUCTION FOR USE	10
	4.1 Operating the product.....	10
	4.2 Adjusting the height.....	11
	4.3 Lock Washbasin into Dock-in	11
	4.4 Permanent lock	12
	4.5 Deactivation of the lock	12
	4.6 Installation of product	12
	4.6.1 Components	13
	4.7 Mounting.....	14
	4.8 Installation interfaces.....	22
5.	SAFETY IN USE	23
6.	CLEANING AND MAINTENANCE	24
	6.1 Cleaning of the washbasin and Dock-in	24
	6.2 Repair of washbasin.....	24
	6.3 Maintenance.....	24
	6.4 Service schedule	25
7.	COMPONENTS PART LIST	26
8.	ENVIRONMENTAL PROTECTION	26
9.	COMPLAINTS.....	26

1. Symbols used in this manual

Warning Symbol Indication of potentially hazardous situation. If not avoided, it can result in serious injury or death.	
Caution Symbol Indication of potentially hazardous situation which may result in minor or moderate injury. It may also be used to alert against unsafe practices.	
Notification Symbol This symbol is used to notify correct use and handling of the product.	

2. General safety

	<p>This manual must be read and understood before use. Always keep this manual in close proximity of the product.</p> <p>The use, installation and service of this product must be in compliance with this manual to avoid accidents and serious personal injury.</p> <p>Never use or handle this product in other ways specified in this manual as it can result in personal safety hazards and/or cause damage to the product.</p> <p>Persons installing and/or using this product either as operator or user should have the necessary safety information and access to this manual.</p> <p>If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified designated persons in order to avoid a hazard.</p>
--	--



Do not perform repairs, disassembly or assembly operations, add-ons, re-adjustments or modification of the product beyond what is described in this manual. These must be carried out by Ropox or Ropox authorized personnel. Do not perform service while in use.

This appliance can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved. Children shall not play with the appliance. Cleaning and user maintenance shall not be made by children without supervision.

Do not use the product if it has defects or have become damaged before being repaired or replaced.
If the control box makes unusual noise or smells, switch off the mains voltage immediately.

Take care that the cables are not damaged.

Unplug the mains cable on mobile equipment before it is moved.

The products must only be used in an environment that corresponds to their IP protection.






The information in this manual is based on correct installation in accordance with installation instructions for this product.

Ropox cannot be held liable if the product is used in any way that differs from stated in this manual and/or installation instruction.

Ropox reserve the right to amend this manual and reference documents without prior notice.

2.1 Product Unit label



	This product is UKCA-marked in accordance with: UK SI 2002 No. 618 - <i>The Medical Devices Regulations 2002</i> , and its amendments
	This product is CE-marked in accordance with: European Medical Device Regulation (EU)2017/745 Council Directive 2011/65/EU, RoHS
	Manufacturer name and address
	Date of production
	Stock number
	Serial number
	Consult manual for important safety related information, warnings and safety precautions.
	Do not dispose as unsorted municipal waste. Product must be returned to a designated recycling station.
	Operating and storing temperatures may not exceed 5-40C°
	Consult the instructions for use

3. General requirements

3.1 Product information

Manufacturer	Ropox A/S Ringstedgade 221 DK-4700 Naestved +45 55 75 05 00 Info@ropox.com	UK Responsible Person	Qserve Group UK, Ltd 49 Greek Street, W1D 4EG London United Kingdom +44 740 885 936 3 info@qservegroup.com
Product models	Part number	Model	Configuration
	40-40071 40-40072	Ropox Swing washbasin Ropox Swing washbasin	Complete Right Complete Left
Basic UDI	57075810001QV		
Expected service life	5 years		
MDR Class 2017/745	Class I		
Intended environments	This product is to be used only in: Professional Healthcare Environment Homecare Environment		
Maximum user weight according to ISO 17966	245kg / 539lbs when the wash basin is locked in dock-in 80kg / 176lbs when Washbasin is free standing		
Height adjustment	15 cm		
Ambient temperature	-10 °C to +50 °C Transport and storage +5 °C to +40 °C Operation		
Relative humidity	20% to 80% - non-condensing		
Materials in contact with patient	Wash basin	Molded marble	
	Unit	Sand cast aluminum Stainless steel tube Various plastic components	
	Cover	ABS	

3.2 Product description

Ropox QuickWash is a small height adjustable system for a washbasin. It can be height adjusted 14 cm, while also projecting the attached washbasin 20cm out from the wall for added legroom.

3.3 Intended use

The Swing Washbasin is a washbasin which can be swung to the user, which makes it possible for the user to wash hands before leaving the toilet. This increases the hygiene, makes the user more self-reliant and gives the assistant better working conditions. The Swing washbasin is available with manual height adjustment. Depending on the model, the height adjustment range is 15 cm for models without dock-in and 20 cm for models with dock-in. This means that the user and carer can set the level of the sink to the height that fits the user's needs. The height adjustment also makes the sink suited for both standing and seated use. It can be lowered for seated users, e.g., wheelchair users or elderly users who prefer to sit while washing hands or brushing teeth, and it can be raised for standing users or carers.

3.4 Intended operator

The intended operator may include all that have read and understood this manual exempt kids.

3.5 Essential performance

The device does not have any function related to basic safety or essential performance. In case of loss or degradation of performance, the user can still wash their hands or chose not to.

3.6 Non-clinical functions



Height adjusting offers better ergonomics to the user.

3.7 Clinical functions

This product does not offer clinical benefit for patients, when used as intended by the manufacturer.

3.8 Product dimensions

40-40071 Left



NB: All dimensions are in mm and inches

3.9 Connection adapters

The highlighted components can be bought separately depending on the type of building installation requirements.


Water supply

Swing Washbasin	Hose from basin	Adapters	Installation in room (not included)
	 10mm	 10mm -> 1/2" Item no. 97001667	 1/2" Thread
		 10mm -> 3/8" Item no. 97001668	 3/8" Thread
		 10mm -> 15mm Item no. 97001665	 15mm Pipe



Water hose extensions

Hose from basin	Coupling piece	Extra hose
 10mm	 10mm -> 1/2" Item no. 97001101	 1/2" x 1/2", 0,5m, steel Item no. 97001123
		 1/2" x 1/2", 1m, plastic Item no. 97001120

Drain



Swing Washbasin	Drain pipe from basin	Adapters	Installation in room (not included)
	 Ø32	No adapter necessary	Ø32
		 Ø32 -> Ø40 Item no. 97001660	 Ø40
		 Ø32 -> Ø50 Item no. 97001661	 Ø50

Drain pipe extensions

Drain pipe from basin	Coupling piece	Extra drain pipe
 Ø32	 Ø32-Ø32 Item no. 97001062	 Ø32 Flex hose, 27-62cm Item no. 97001162
		 Ø32 Flex hose, 40-110cm Item no. 97001161

3.10 Layout proposals

For complete layout proposals & inspiration contact Ropox for further guidance.



4. Instruction for use

4.1 Operating the product



Ropox Swing Washbasin has a turning function, which means that it is **NOT** allowed to be used as a walking or standing support.



If the washbasin is locked in the Dock-in it functions as a standard washbasin and is safe to use as a standing support.

Maximum loads

Locked in Dock-in (sold separately)

A 245kg/539lbs person is able to lean on the basin while standing, without causing any significant deformation or safety risk.

Washbasin free standing

An 80kg/176lbs person is able to lean on the basin while standing without causing any significant deformation or safety risk.



Warning!

Make sure that the wash basin is locked correctly in dock-in, when using it as a standing support.



Caution!

Do not sit or fully displace your body weight on the sink or on the swing arm.

4.2 Adjusting the height

For height adjustment, turn handle.



Warning!

The product should always be able to travel the full range of actuation without colliding with objects. Failing to do so will compromise the product stability.

4.3 Lock Washbasin into Dock-in

The Dock-in station is designed to ensure easy locking of the washbasin during daily use.

The washbasin is guided into the notch and will be locked automatically in the right position. To release the washbasin pull one of the two handles. This will release the washbasin from the locking mechanism after which it may swing freely.



Warning!

Make sure that no items should be placed between the wash basin and the dock, when docking in

4.4 **Permanent lock**

The washbasin can be permanently locked and thereby function as a standard washbasin. This is done by inserting the two supplied M5 screws as shown below. Please note that the washbasin needs to be locked in the Dock-in when the screws are tightened and both screws must be used.



4.5 **Deactivation of the lock**

It is also possible to use the screws to deactivate the locking system if desired. This is done by inserting and tightening one of the screws while pulling out the handle. This only has to be done in one of the sides to work.



4.6 **Installation of product**

The screws and rawplugs included are for mounting on a concrete wall. The installer must always examine the material, condition and strength of the wall and use appropriate screws and rawplugs. Maximum load of top screws is 120kg/264lbs.



Warning!

The fitter should always consider the material, condition and strength of the wall and use screws and rawplugs suitable for the specific wall type.



4.6.1 Components



With the purchase, and for the assembly of this product, the following components are included.

Lifting unit	1 stk.	
Inside cover plate	1 stk.	
Outer cover plate	1 stk.	
Bracket for inside cover plate	2 stk.	
Wash basin	1 stk.	
Dock-in	1 stk.	
Bracket for dock-in	2 stk.	
U-profile with nut	2 stk.	
Handle	1 stk.	
Countersunk screw M6x16	8 stk.	
Screw M4x6	2 stk.	
Machine screw M4x16	1 stk.	
Screw M5x6	2 stk.	
Frame screw 7,5x72mm	10 stk.	
Rawlplugs 10x61mm	10 stk.	



4.7 Mounting



For recommended height of washbasin from 750-950mm (29.5 - 37.4 in) above floor level, see below mentioned dimensions.






Mount fitting for fixation of inside cover as illustrated.
 If washbasin is placed in opposite side fittings & dimension have to be swapped.











Mount washbasin into frame

Move washbasin into top position. Mount 2 M5x6 screws under the cover each side. This is to avoid washbasin being pulled out.
NOTE! It is important that slide bearings are mounted from underneath.



Connect drain pipe & connecting hoses.






Ø10

Ø32

Ø10








There is a small piece of velcro attached to backside of inside cover. After mounting of screws, move washbasin into bottom position. Remove protection paper from velcro, hold inside cover up and position close to outer cover and push against the wall until velcro sticks to wall.



Turn washbasin in against the cover. Place if possible a spirit level onto washbasin. For fitting of fixation of Dock-in to be fastened in correct height loosen fittings a little & adjust them to leave approx. 33mm between fittings & spirit level. Afterwards fasten fittings thoroughly with a spanner.





Test that washbasin freely can be swung into Dock-in and locks like it should. If washbasin is not positioned satisfactorily, fittings of Dock-in have to be loosened & either raised or lowered a little.



Note!

If the wash basin is delivered with a touchless mixer tab, this might need to be calibrated to accommodate the specific light settings in the room as well as any individual user needs. The calibration has to be done according to the user manual of the mixer tab which is supplied with the wash basin.

5. Safety in use

- The Ropox Swing Washbasin and Dock-in should only be used by people, who have read and understood these instructions.
- Always use the washbasin so there is no risk of damage to people or property. The person, who operates the Ropox Swing Washbasin, is responsible for avoiding damage or injury.
- Children or persons with reduced observation capability should only use the washbasin when supervised.
- If the washbasin is used in publicly accessible locations where children or people with reduced observation ability may get close to the Ropox Swing Washbasin, the person operating the washbasin must pay sufficient attention in order to prevent dangerous situations.
- Do not operate the washbasin in case of defects or damage.
- Do not overload the washbasin.
- Modifications, which may influence the operation or construction of the washbasin, are not allowed.
- Installation, service and repairs must be carried out by competent personnel.
- If the washbasin has not been assembled according to these mounting instructions the right to complain may become void.
- Only use Ropox original spare parts as replacement parts. If other spare parts are used, the right to complain may become void.
- Keep notice that there is no overflow build into the washbasin. Only use Ropox' overflow plug to fill the washbasin. Overflow of water can cause slippery floor and should be avoided to minimize the risk of slipping or falling.
- To avoid risk of pinching be aware not to place your hand between the washbasin and dock-in when locked in position.
- Be aware to check that the washbasin is properly locked in place in the dock-in before applying any loads.
- The washbasin may only be applied to personal hygiene purposes.
- Do not lean on the accessories attached to the washbasin.
- To avoid entrapment do not place you head or body parts between the water connection hose and the swinging arm.
- Be aware that the washbasin might be slippery if covered in water and soap.

6. Cleaning and Maintenance

	<p>Note!</p> <p>Do not use cleaning agents containing abrasive e.g. scouring powder, steel wool, scouring sponge.</p> <p>This product is not designed to be sterilized, autoclaving and sterilization beyond normal cleaning is may possibly change the product safety and function.</p>
---	---

6.1 Cleaning of the washbasin and Dock-in

It is important that the washbasin is cleaned according to these guidelines.

Clean the washbasin with a wrung cloth with lukewarm water and a mild detergent. Do not use abrasives or grinding cloths, brushes or sponges.

Ropox Swing washbasin is made of a composite material of marble and plastic granulate with a gel coat surface. This gives a hard and very hardwearing finish, which is easy to clean. Wash the surfaces daily with water and dry with a cloth. Do not use detergents containing hard abrasives – e.g. steel wool, scouring powder or sulfuric acid.

If the water has high calcium content, calcareous deposits will often occur. These deposits should be removed at least once a week by using a detergent containing citric acid, acetic acid or phosphoric acid. Leave the detergent to work for 5 to 10 minutes depending on the thickness of the deposits and clean thoroughly with a soft scouring sponge.

Disinfection of the basin may be done with household spirits.

6.2 Repair of washbasin

Minor damage or limited discolorations of the surfaces of the washbasin itself may easily be repaired by means of a special repair kit. Please contact Ropox for further details.

6.3 Maintenance

	<p>Note!</p> <p>Failing to comply with periodic maintenance may result of degrading of product function and safety.</p> <p>Inspections, service and repairs must be carried out by competent personnel.</p>
---	--

The washbasin is maintenance-free and the moving parts have been lubricated for life. For reasons of safety and reliability we recommend inspection of the washbasin once a year:

Check that all bolts have been securely tightened.
Check that the washbasin rotates freely and that the arm swings properly

After each inspection, fill in the service schedule.

Only use Ropox original spare parts for replacement of parts. If other spare parts are used, the right to complain may become void.

6.4 Service schedule

Service	Serial no.
Date:	_____
Signature:	_____
Comments:	_____

Service	Serial no.
Date:	_____
Signature:	_____
Comments:	_____

Service	Serial no.
Date:	_____
Signature:	_____
Comments:	_____

Service	Serial no.
Date:	_____
Signature:	_____
Comments:	_____

Service	Serial no.
Date:	_____
Signature:	_____
Comments:	_____

Service	Serial no.
Date:	_____
Signature:	_____
Comments:	_____

7. Components part list



Note!

Ropox will make parts list available for extraordinary maintenance and repair beyond what is described in this manual. Repair beyond what is described in this manual may only be done by Ropox designated service personnel.

8. Environmental protection

The product is not intended to be disposed as municipal waste. Proper disassembly, sorting and disposal of components must be done by waste disposal professionals.



Part	Disposal recommendation
Wash basin	Ceramic
Main unit	Steel
Faucet	Steel
Cover	Aluminum

9. Complaints

See our general terms of sale and delivery on www.ropox.com



ROPOX A/S

Ringstedgade 221
DK – 4700 Næstved

Tel.: +45 55 75 05 00 Fax.: +45 55 75 05 50

E-mail: info@ropox.dk

www.ropox.com